



Mila Effects

Glory

PRODUCT TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Mila Effects Glory is a premium decorative effect paint that creates an intense shimmer and a luxurious depth effect on the surface with its bold pearl particles.

PRODUCT DETAILS

Mila Effects Glory is a premium decorative effect paint that creates an intense shimmer and a luxurious depth effect on the surface with its bold pearl particles. Fine-textured with bold pearl particles, giving a luxurious, deep surface effect that shines intensely in light. Applied by Mila's application team with a brush or special tools in directional, controlled movements. With Mila's application and design solutions, it delivers a durable, aesthetically lasting result on every surface. Areas of use: interior and exterior facades, on all suitable surface-prepared substrates.

FEATURES

- **Strong sheen with bold pearl particles:** Pearl particles bolder than Safir create an intense, striking shimmer on the surface.
- **Voluminous reflection with light:** Offers a rich, voluminous sheen that changes with lighting.
- **Premium, striking character:** Its luxurious depth effect gives spaces a prestigious focal surface.

AREAS OF USE

- Suitable for interior and exterior use on all suitable surface-prepared substrates.
- The surface must be dry, clean and prepared with a base coat; free of dust and loose residues.

APPLICATION

Base: Applied over a suitable base coat after the base is fully dry.

Application method: Applied with a brush or special tools in directional, controlled movements.

Direction and shimmer: Keeping the direction of movement achieves an intense, voluminous pearl shimmer.

Application conditions: Work between +5°C and +35°C; protect the surface from direct sun, wind and precipitation.

SURFACE / TEXTURE

Fine-textured with bold pearl particles; a luxurious, deep surface effect that shines intensely in light.



Suitable for Exteriors



Washable



Repaintable




Water-Based

Mila Effects — Glory

Technical Reference

APPLICATION SYSTEM



TECHNICAL DATA

Appearance / form	Viscous liquid
Colour	According to the colour chart
Finish / gloss	Pearlescent (bold)
pH	8 – 9
Density	1.10 – 1.30 g/cm ³
Solid content	~40 – 50 %
Viscosity	Medium (viscous)
Flash point	Not applicable (water-based)
Flammability	Non-flammable

COVERAGE

4.67–6 m²/kg

Coverage varies by surface smoothness/absorbency, primer performance, application thickness and the targeted surface character.

DRYING TIME

- Surface Drying: 1–3 hours (depending on ambient conditions)
- Full Cure: 24–72 hours (depending on product type and application thickness)

PACKAGING

1 kg, 2.5 kg, 7.5 kg, 15 kg

STORAGE

Shelf life is 2 years when stored unopened in its original packaging, in a cool, dry place away from direct sunlight (+5°C to +35°C).

CLIMATE & REGIONAL GUIDANCE

- Cool / humid or coastal air (high RH): cure and recoat times lengthen — extend intervals, confirm the substrate is dry (< 5 %) and ventilate; do not apply near the dew point.
- Hot / dry inland air: the surface skins quickly — work in shade, avoid midday sun, keep a wet edge and do not over-thin.
- Temperature: apply between +5 °C and +35 °C; cooler slows cure, warmer accelerates it.

APPLICATION CONDITIONS

- Ambient & substrate temperature +5 °C to +35 °C (41–95 °F)
- Relative humidity below 80 %
- Substrate moisture below 5 %
- Do not apply in direct sun, rain, fog or strong wind; protect fresh work for 24–48 h

TOOLS

Brush

SUITABLE SUBSTRATES

- ✓ Prepared interior and exterior walls with a base coat applied
- ✓ Fully cured, dust-free and even base-coat surface

NOT SUITABLE FOR

- ✗ Directly on concrete, exposed concrete and cement-based render (without a base coat / primer)
- ✗ Directly on gypsum board, gypsum plaster and brick (without a base coat / primer)
- ✗ Continuously wet or water-immersed surfaces
- ✗ Chalking, friable or non-adhering surfaces (without consolidation)
- ✗ Frozen, frosty or surfaces below +5 °C

CLEANING

Clean tools with water immediately after use, while the product is still wet.

MAINTENANCE

Clean the cured surface with a soft cloth and a mild, non-abrasive detergent. Avoid aggressive solvents and abrasive pads. Allow full cure before cleaning or heavy use.

ON-SITE REPAIR & TOUCH-UP

1. Clean the damaged area; remove any loose or flaking material.
2. Feather-sand the edges; fill deeper defects with Multifiller and re-prime if bare substrate is exposed.
3. Re-apply the same product with the original tool/technique, blending outward to a natural break (corner, edge or plane change).
4. Where used, re-apply the protective topcoat over the repaired area.

Decorative finishes may show a slight variation at repair edges; blend to a natural break and keep colour/batch records for accurate matching.

Mila Effects — Glory

Safety & Regulatory

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

Contains: 2-methylisothiazol-3(2H)-one (MIT), 1,2-benzisothiazol-3(2H)-one (BIT)

PRECAUTIONARY STATEMENTS

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.

Note: For more information, please review the product Safety Data Sheet (SDS).

This technical document is based on data obtained under standard laboratory conditions. For matters not specified herein, approval must be obtained from our technical team; otherwise our company cannot be held responsible for application errors arising from incomplete information. We reserve the right to make changes to the content. For detailed risks and precautions regarding health, safety and transport, the Safety Data Sheet (SDS) must be reviewed.



MİLA PROJE MAĞAZACILIK ANONİM ŞİRKETİ

📍 Mehmet Akif Ersoy Mah. Ünvan Sok. No:11-13A Arnavutköy / İstanbul
☎ 0212 445 4544 ✉ info@milaturkiye.com www.milaturkiye.com



MİLA PRODUCT TECHNICAL DATA SHEET