



Mila Effects

Tones

PRODUCT TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Mila Effects Tones is a premium effect paint that creates a matured, characterful look with depth on the surface through a patina effect.

PRODUCT DETAILS

Mila Effects Tones is a premium effect paint that creates a matured, characterful look with depth on the surface through a patina effect. Patina-character, layered and tone-transitioned, giving a decorative surface with an aged appearance. Applied by Mila's application team with a roller over a base coat, then wiped with a sponge to create the aged effect. With the expertise of Mila's application team, it delivers a durable, aesthetically lasting result on every surface. Areas of use: interior and exterior facades, on all suitable surface-prepared substrates.

FEATURES

- **Layered structure with a natural patina feel:** Layered application creates a patina effect that looks matured over time.
- **Tone transitions that shift with light:** Offers a lively surface with vivid tone transitions that change with lighting.
- **Aged, timeless character:** Its sophisticated, aged look gives spaces a deep-rooted atmosphere.

AREAS OF USE

- Used on interior and exterior facades, over fully cured mineral effect coatings (Betonup, Sart, Mone, Marmo, Granito, Terrazzo).
- The underlying coating must be dry, clean and fully cured.

APPLICATION

Substrate: Applied over fully cured mineral effect coatings (Betonup, Sart, Mone, Marmo, Granito, Terrazzo).

Application method: Applied and wiped back with a sponge, cloth, roller or brush to create the patina effect.

Ageing: Wiped with a sponge before it dries to create the aged effect, building patina depth and tone movement.

Application conditions: Work between +5°C and +35°C; protect the surface from direct sun, wind and precipitation.

SURFACE / TEXTURE

Patina-character, layered and tone-transitioned; a decorative surface with an aged appearance.



Suitable for Exteriors



Washable



Repaintable



Water-Based

Technical Reference

APPLICATION SYSTEM

- 1 Allow the mineral effect coating (Betonup, Sart, Mone, Marmo, Granito, Terrazzo) to cure fully →
- 2 Tones — applied and wiped back to create the patina effect →
- 3 Optional protective topcoat (Aqua / Corex)

TECHNICAL DATA

Appearance / form	Viscous liquid
Colour	According to the colour chart
Finish / gloss	Matt (patina)
pH	8 – 9
Density	1.10 – 1.30 g/cm³
Solid content	~40 – 50 %
Viscosity	Medium (viscous)
Flash point	Not applicable (water-based)
Flammability	Non-flammable

COVERAGE

6.67–10 m²/kg

Coverage varies by surface smoothness/absorbency, primer performance, application thickness and the targeted surface character.

DRYING TIME

- Surface Drying: 1–3 hours (depending on ambient conditions)
- Full Cure: 24–72 hours (depending on product type and application thickness)

PACKAGING

1 kg, 2.5 kg, 7.5 kg, 15 kg

STORAGE

Shelf life is 2 years when stored unopened in its original packaging, in a cool, dry place away from direct sunlight (+5°C to +35°C).

CLIMATE & REGIONAL GUIDANCE

- Cool / humid or coastal air (high RH): cure and recoat times lengthen — extend intervals, confirm the substrate is dry (< 5 %) and ventilate; do not apply near the dew point.
- Hot / dry inland air: the surface skins quickly — work in shade, avoid midday sun, keep a wet edge and do not over-thin.
- Temperature: apply between +5 °C and +35 °C; cooler slows cure, warmer accelerates it.

APPLICATION CONDITIONS

- Ambient & substrate temperature +5 °C to +35 °C (41–95 °F)
- Relative humidity below 80 %
- Substrate moisture below 5 %
- Do not apply in direct sun, rain, fog or strong wind; protect fresh work for 24–48 h

TOOLS

Sponge / cloth · Roller · Brush

SUITABLE SUBSTRATES

- ✓ Fully cured mineral effect coatings (Betonup, Sart, Mone, Marmo, Granito, Terrazzo)

NOT SUITABLE FOR

- ✗ Directly on concrete, exposed concrete and cement-based render (without a base coat / primer)
- ✗ Directly on gypsum board, gypsum plaster and brick (without a base coat / primer)
- ✗ Continuously wet or water-immersed surfaces
- ✗ Chalking, friable or non-adhering surfaces (without consolidation)
- ✗ Frozen, frosty or surfaces below +5 °C

CLEANING

Clean tools with water immediately after use, while the product is still wet.

MAINTENANCE

Clean the cured surface with a soft cloth and a mild, non-abrasive detergent. Avoid aggressive solvents and abrasive pads. Allow full cure before cleaning or heavy use.

ON-SITE REPAIR & TOUCH-UP

1. Clean the damaged area; remove any loose or flaking material.
2. Feather-sand the edges; fill deeper defects with Multifiller and re-prime if bare substrate is exposed.
3. Re-apply the same product with the original tool/technique, blending outward to a natural break (corner, edge or plane change).
4. Where used, re-apply the protective topcoat over the repaired area.

Decorative finishes may show a slight variation at repair edges; blend to a natural break and keep colour/batch records for accurate matching.

Mila Effects — Tones

Safety & Regulatory

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

Contains: 2-methylisothiazol-3(2H)-one (MIT), 1,2-benzisothiazol-3(2H)-one (BIT)

PRECAUTIONARY STATEMENTS

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.

Note: For more information, please review the product Safety Data Sheet (SDS).

This technical document is based on data obtained under standard laboratory conditions. For matters not specified herein, approval must be obtained from our technical team; otherwise our company cannot be held responsible for application errors arising from incomplete information. We reserve the right to make changes to the content. For detailed risks and precautions regarding health, safety and transport, the Safety Data Sheet (SDS) must be reviewed.



MİLA PROJE MAĞAZACILIK ANONİM ŞİRKETİ

📍 Mehmet Akif Ersoy Mah. Ünvan Sok. No:11-13A Arnavutköy / İstanbul

☎ 0212 445 4544

✉ info@milaturkiye.com

www.milaturkiye.com



MİLA PRODUCT TECHNICAL DATA SHEET