



Mila Primera

Multifiller

PRODUCT TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

A water-based, multi-purpose filler developed for interior and exterior facades. It fills cracks, gaps and defects on the surface to create a smooth base for paints and coatings.

PRODUCT DETAILS

Mila Primera Multifiller is a water-based, multi-purpose filler developed for interior and exterior facades. It fills cracks, gaps and defects on the surface to create a smooth base for paints and coatings. A smooth, filled repair surface. Applied by Mila's application team with a steel trowel or spatula. The surface must be clean, dry and sound. After drying, light sanding can be done if needed before proceeding with the paint/coating. With Mila's application and design service, it delivers a durable, aesthetically lasting result on every surface. Areas of use: interior and exterior facades; used to repair cracks, gaps and surface defects on concrete, plaster, gypsum and mineral surfaces.

FEATURES

- **High filling power:** Effectively fills cracks, gaps and surface defects.
- **No cracking:** Its balanced structure resists cracking after drying.
- **Easy to sand, smooth base:** Sands easily to create a neat base for paints and coatings.

AREAS OF USE

- Used to repair cracks, gaps and surface defects on interior and exterior facades; on concrete, plaster, gypsum and mineral surfaces.
- The surface must be dry, clean and sound.

APPLICATION

Application method: Applied with a steel trowel or spatula.
Sanding: After drying, light sanding is done if needed.
Topcoat: Proceed with the paint or coating application.
Application conditions: Work between +5°C and +35°C; protect the surface from direct sun, wind and precipitation.


SURFACE / TEXTURE

A smooth, filled repair surface.

Mila Primera — Multifiller

Technical Reference

APPLICATION SYSTEM



TECHNICAL DATA

Appearance / form	Paste (surfacing filler)
Colour	White
Finish / gloss	N/A (filler)
pH	8 – 9
Density	1.60 – 1.80 g/cm³
Solid content	~75 – 85 %
Viscosity	High (paste)
Flash point	Not applicable (water-based)
Flammability	Non-flammable

COVERAGE

1–2 m²/kg

Coverage varies by surface smoothness/absorbency, primer performance, application thickness and the targeted surface character.

DRYING TIME

- Surface Drying: 1–3 hours (depending on ambient conditions)
- Full Cure: 24–72 hours (depending on product type and application thickness)

PACKAGING

3.5 kg, 10 kg, 20 kg

STORAGE

Shelf life is 2 years when stored unopened in its original packaging, in a cool, dry place away from direct sunlight (+5°C to +35°C).

CLIMATE & REGIONAL GUIDANCE

- Cool / humid or coastal air (high RH): cure and recoat times lengthen — extend intervals, confirm the substrate is dry (< 5 %) and ventilate; do not apply near the dew point.
- Hot / dry inland air: the surface skins quickly — work in shade, avoid midday sun, keep a wet edge and do not over-thin.
- Temperature: apply between +5 °C and +35 °C; cooler slows cure, warmer accelerates it.

APPLICATION CONDITIONS

- Ambient & substrate temperature +5 °C to +35 °C (41–95 °F)
- Relative humidity below 80 %
- Substrate moisture below 5 %
- Do not apply in direct sun, rain, fog or strong wind; protect fresh work for 24–48 h

TOOLS

Steel trowel · Spatula

SUITABLE SUBSTRATES

- ✓ Cracks, gaps and defects on concrete, plaster, gypsum and mineral surfaces

NOT SUITABLE FOR

- ✗ Structural / moving joints
- ✗ Permanently wet areas
- ✗ Deep voids in a single pass (build up in layers)

CLEANING

Clean tools with water immediately after use, while the product is still wet.

MAINTENANCE

Clean the cured surface with a soft cloth and a mild, non-abrasive detergent. Avoid aggressive solvents and abrasive pads. Allow full cure before cleaning or heavy use.

ON-SITE REPAIR & TOUCH-UP

1. Clean the damaged area; remove any loose or flaking material.
2. Feather-sand the edges; fill deeper defects with Multifiller and re-prime if bare substrate is exposed.
3. Re-apply the same product with the original tool/technique, blending outward to a natural break (corner, edge or plane change).
4. Where used, re-apply the protective topcoat over the repaired area.

Decorative finishes may show a slight variation at repair edges; blend to a natural break and keep colour/batch records for accurate matching.

Mila Primera – Multifiller

Safety & Regulatory

HAZARD STATEMENTS

The product is not classified as hazardous according to Regulation (EC) No 1272/2008 (CLP) and the Turkish SEA/KKDİK Regulation.

EUH208 Contains 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

PRECAUTIONARY STATEMENTS

- P102 Keep out of reach of children.
- P262 Do not get in eyes, on skin, or on clothing.
- P501 Dispose of contents/container in accordance with local/national regulations.

Note: For more information, please review the product Safety Data Sheet (SDS).

This technical document is based on data obtained under standard laboratory conditions. For matters not specified herein, approval must be obtained from our technical team; otherwise our company cannot be held responsible for application errors arising from incomplete information. We reserve the right to make changes to the content. For detailed risks and precautions regarding health, safety and transport, the Safety Data Sheet (SDS) must be reviewed.



MİLA PROJE MAĞAZACILIK ANONİM ŞİRKETİ

📍 Mehmet Akif Ersoy Mah. Ünvan Sok. No:11-13A Arnavutköy / İstanbul

☎ 0212 445 4544

✉ info@milaturkiye.com

www.milaturkiye.com



MİLA PRODUCT TECHNICAL DATA SHEET