



Mila Primera

Universal Primer

PRODUCT TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

A water-based, silicone interior and exterior primer. Tintable; it can be brought to the same color as the topcoat. It balances absorbency and supports strong grip of the paint to the surface.

PRODUCT DETAILS

Mila Primera Universal Primer is a water-based, silicone interior and exterior primer. It is tintable and can be brought to the same color as the topcoat. It balances absorbency and supports strong grip of the paint to the surface. A tintable, absorbency-balancing primer surface. Applied by Mila's application team with a brush, roller or airless spray. The surface must be clean, dry and sound. After drying, proceed with the paint or coating. With Mila's experienced application team, it delivers a durable, aesthetically lasting result on every surface. Areas of use: interior and exterior facades; used as a primer on concrete, plaster, gypsum and previously painted surfaces before paint and coating applications.

FEATURES

- **Silicone multi-purpose structure:** Its silicone content provides strong adhesion across a wide range of interior and exterior surfaces.
- **Tintable:** Bringing it to the same color as the topcoat improves opacity and application efficiency.
- **Balances absorbency:** Regulates surface absorbency to support homogeneous grip of the paint.

AREAS OF USE

- Used as a primer on interior and exterior facades; on concrete, plaster, gypsum and previously painted surfaces before paint and coating applications.
- The surface must be dry, clean and sound; free of dust, grease and loose residues.

APPLICATION

Surface preparation: Clean the surface; remove dust, grease and loose particles.

Application method: Applied with a brush, roller or airless spray.

Drying: After drying, proceed with the paint or coating application.

Application conditions: Work between +5°C and +35°C; protect the surface from direct sun, wind and precipitation.


SURFACE / TEXTURE

A tintable, absorbency-balancing primer surface.

Mila Primera — Universal Primer

Technical Reference

APPLICATION SYSTEM



TECHNICAL DATA

Appearance / form	Liquid (primer)
Colour	Transparent / tintable
Finish / gloss	Matt (primer)
pH	8.5 – 9.0
Density	1.40 – 1.55 g/cm ³
Solid content	~55 – 65 %
Viscosity	Viscous
Flash point	Not applicable (water-based)
Flammability	Non-flammable

COVERAGE

4.5–6.5 m²/kg

Coverage varies by surface smoothness/absorbency, primer performance, application thickness and the targeted surface character.

DRYING TIME

- Surface Drying: 1–3 hours (depending on ambient conditions)
- Full Cure: 24–72 hours (depending on product type and application thickness)

PACKAGING

3.5 kg, 10 kg, 20 kg

STORAGE

Shelf life is 2 years when stored unopened in its original packaging, in a cool, dry place away from direct sunlight (+5°C to +35°C).

CLIMATE & REGIONAL GUIDANCE

- Cool / humid or coastal air (high RH): cure and recoat times lengthen — extend intervals, confirm the substrate is dry (< 5 %) and ventilate; do not apply near the dew point.
- Hot / dry inland air: the surface skins quickly — work in shade, avoid midday sun, keep a wet edge and do not over-thin.
- Temperature: apply between +5 °C and +35 °C; cooler slows cure, warmer accelerates it.

APPLICATION CONDITIONS

- Ambient & substrate temperature +5 °C to +35 °C (41–95 °F)
- Relative humidity below 80 %
- Substrate moisture below 5 %
- Do not apply in direct sun, rain, fog or strong wind; protect fresh work for 24–48 h

TOOLS

Brush · Roller · Airless spray · Trowel

SUITABLE SUBSTRATES

- ✓ Concrete and exposed concrete
- ✓ Cement / lime render and gypsum plaster
- ✓ Gypsum board and mineral surfaces
- ✓ Sound, previously painted interior and exterior surfaces

NOT SUITABLE FOR

- ✗ Continuously wet or water-immersed surfaces
- ✗ Untreated or rusting metal (without a suitable primer)
- ✗ Chalking, friable or non-adhering surfaces (without consolidation)
- ✗ Frozen, frosty or surfaces below +5 °C

CLEANING

Clean tools with water immediately after use, while the product is still wet.

MAINTENANCE

Clean the cured surface with a soft cloth and a mild, non-abrasive detergent. Avoid aggressive solvents and abrasive pads. Allow full cure before cleaning or heavy use.

ON-SITE REPAIR & TOUCH-UP

1. Clean the damaged area; remove any loose or flaking material.
2. Feather-sand the edges; fill deeper defects with Multifiller and re-prime if bare substrate is exposed.
3. Re-apply the same product with the original tool/technique, blending outward to a natural break (corner, edge or plane change).
4. Where used, re-apply the protective topcoat over the repaired area.

Decorative finishes may show a slight variation at repair edges; blend to a natural break and keep colour/batch records for accurate matching.

Mila Primera – Universal Primer

Safety & Regulatory

HAZARD STATEMENTS

The product is not classified as hazardous according to Regulation (EC) No 1272/2008 (CLP) and the Turkish SEA/KKDİK Regulation.

EUH208 Contains 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

PRECAUTIONARY STATEMENTS

- P102 Keep out of reach of children.
- P262 Do not get in eyes, on skin, or on clothing.
- P501 Dispose of contents/container in accordance with local/national regulations.

Note: For more information, please review the product Safety Data Sheet (SDS).

This technical document is based on data obtained under standard laboratory conditions. For matters not specified herein, approval must be obtained from our technical team; otherwise our company cannot be held responsible for application errors arising from incomplete information. We reserve the right to make changes to the content. For detailed risks and precautions regarding health, safety and transport, the Safety Data Sheet (SDS) must be reviewed.



MİLA PROJE MAĞAZACILIK ANONİM ŞİRKETİ

📍 Mehmet Akif Ersoy Mah. Ünvan Sok. No:11-13A Arnavutköy / İstanbul
☎ 0212 445 4544 ✉ info@milaturkiye.com www.milaturkiye.com



MİLA PRODUCT TECHNICAL DATA SHEET