



Mila Protect

Prestige Wax

PRODUCT TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Prestige Wax is a finishing polish that adds gloss and depth to marble-effect decorative coatings.

PRODUCT DETAILS

Mila Protect Prestige Wax is a finishing polish that adds gloss and depth to marble-effect decorative coatings. A glossy, depth-enhancing premium topcoat. Applied by the Mila application team in a thin coat; once dry, the finish is obtained by polishing with a cloth or pad. With Mila's application and design solutions, it delivers a durable, aesthetically lasting result on every surface. Areas of use: interior spaces, on surfaces where a marble-effect coating has been applied and has fully dried.

FEATURES

- **Gloss and depth effect:** Gives the surface a premium gloss and visual depth.
- **Emphasises the marble effect:** Strengthens the perception of veining and depth on marble-look coatings.
- **Premium finish:** Its thin film creates a refined, polished topcoat on the surface.

AREAS OF USE

- Suitable for interior spaces, on surfaces where a marble-effect coating has been applied and has fully dried.
- The surface must be clean, dry and free of dust.

APPLICATION

- Application method:** Applied in a thin coat.
- Polishing:** Once dry, the finish is obtained by polishing with a cloth or pad.
- Application conditions:** Work between +5°C and +35°C in a well-ventilated interior space.


SURFACE / TEXTURE

A glossy, depth-enhancing premium topcoat.

Mila Protect — Prestige Wax

Technical Reference

APPLICATION SYSTEM



TECHNICAL DATA

Appearance / form	Liquid (wax polish)
Colour	According to the colour chart
Finish / gloss	Satin to gloss
pH	8 – 9
Density	0.95 – 1.00 g/cm³
Solid content	~10 – 18 %
Viscosity	Fluid
Flash point	Not applicable (water-based)
Flammability	Non-flammable

COVERAGE

10–12 m²/kg

Coverage varies by surface smoothness/absorbency, primer performance, application thickness and the targeted surface character.

DRYING TIME

- Surface Drying: 1–3 hours (depending on ambient conditions)
- Full Cure: 24–72 hours (depending on product type and application thickness)

PACKAGING

1 kg, 3 kg

STORAGE

Shelf life is 2 years when stored unopened in its original packaging, in a cool, dry place away from direct sunlight (+5°C to +35°C).

CLIMATE & REGIONAL GUIDANCE

- Cool / humid or coastal air (high RH): cure and recoat times lengthen — extend intervals, confirm the substrate is dry (< 5 %) and ventilate; do not apply near the dew point.
- Hot / dry inland air: the surface skins quickly — work in shade, avoid midday sun, keep a wet edge and do not over-thin.
- Temperature: apply between +5 °C and +35 °C; cooler slows cure, warmer accelerates it.

APPLICATION CONDITIONS

- Ambient & substrate temperature +5 °C to +35 °C (41–95 °F)
- Relative humidity below 80 %
- Substrate moisture below 5 %
- Do not apply in direct sun, rain, fog or strong wind; protect fresh work for 24–48 h

TOOLS

Cloth / pad · Polishing machine · Steel trowel

SUITABLE SUBSTRATES

✓ Surfaces coated with Prestige and fully cured

NOT SUITABLE FOR

- ✗ Exterior facades
- ✗ Continuously wet areas
- ✗ Freshly applied, uncured coatings
- ✗ Floors subject to heavy abrasion

CLEANING

Clean tools with water immediately after use, while the product is still wet.

MAINTENANCE

Clean the cured surface with a soft cloth and a mild, non-abrasive detergent. Avoid aggressive solvents and abrasive pads. Allow full cure before cleaning or heavy use.

ON-SITE REPAIR & TOUCH-UP

1. Clean the damaged area; remove any loose or flaking material.
2. Feather-sand the edges; fill deeper defects with Multifiller and re-prime if bare substrate is exposed.
3. Re-apply the same product with the original tool/technique, blending outward to a natural break (corner, edge or plane change).
4. Where used, re-apply the protective topcoat over the repaired area.

Decorative finishes may show a slight variation at repair edges; blend to a natural break and keep colour/batch records for accurate matching.

Mila Protect — Prestige Wax

Safety & Regulatory

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

Contains: 2-methylisothiazol-3(2H)-one (MIT), 1,2-benzisothiazol-3(2H)-one (BIT)

PRECAUTIONARY STATEMENTS

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.

Note: For more information, please review the product Safety Data Sheet (SDS).

This technical document is based on data obtained under standard laboratory conditions. For matters not specified herein, approval must be obtained from our technical team; otherwise our company cannot be held responsible for application errors arising from incomplete information. We reserve the right to make changes to the content. For detailed risks and precautions regarding health, safety and transport, the Safety Data Sheet (SDS) must be reviewed.



MİLA PROJE MAĞAZACILIK ANONİM ŞİRKETİ

📍 Mehmet Akif Ersoy Mah. Ünvan Sok. No:11-13A Arnavutköy / İstanbul
☎ 0212 445 4544 ✉ info@milaturkiye.com www.milaturkiye.com



MİLA PRODUCT TECHNICAL DATA SHEET